


## IR Receiver Module for Light Barrier Systems



19026

### MECHANICAL DATA

**Pinning:**

1 = OUT, 2 = GND, 3 =  $V_S$

### FEATURES

- Low supply current
- Photo detector and preamplifier in one package
- Internal filter for 38 kHz IR signals
- Shielding against EMI
- Supply voltage: 2.7 V to 5.5 V
- Visible light is suppressed by IR filter
- Insensitive to supply voltage ripple and noise
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC




### DESCRIPTION


The TSOP58038 is a compact IR receiver for sensor applications. It has a high gain for IR signals at 38 kHz. The detection level does not change when ambient light or strong IR signals are applied. It can receive continuous 38 kHz signals or 38 kHz bursts.

| PARTS TABLE       |                     |
|-------------------|---------------------|
| CARRIER FREQUENCY | SENSOR APPLICATIONS |
| 38 kHz            | TSOP58038           |

### BLOCK DIAGRAM



### APPLICATION CIRCUIT



The external components  $R_1$  and  $C_1$  are optional to improve the robustness against electrical overstress (typical values are  $R_1 = 100 \Omega$ ,  $C_1 = 0.1 \mu F$ ). The output voltage  $V_o$  should not be pulled down to a level below 1 V by the external circuit. The capacitive load at the output should be less than 2 nF.

\*\* Please see document "Vishay Material Category Policy": [www.vishay.com/doc?99902](http://www.vishay.com/doc?99902)

| ABSOLUTE MAXIMUM RATINGS    |                             |             |                          |      |
|-----------------------------|-----------------------------|-------------|--------------------------|------|
| PARAMETER                   | TEST CONDITION              | SYMBOL      | VALUE                    | UNIT |
| Supply voltage (pin 3)      |                             | $V_S$       | - 0.3 to + 6.0           | V    |
| Supply current (pin 3)      |                             | $I_S$       | 5                        | mA   |
| Output voltage (pin 1)      |                             | $V_O$       | - 0.3 to 5.5             | V    |
| Voltage at output to supply |                             | $V_S - V_O$ | - 0.3 to ( $V_S + 0.3$ ) | V    |
| Output current (pin 1)      |                             | $I_O$       | 5                        | mA   |
| Junction temperature        |                             | $T_j$       | 100                      | °C   |
| Storage temperature range   |                             | $T_{stg}$   | - 25 to + 85             | °C   |
| Operating temperature range |                             | $T_{amb}$   | - 25 to + 85             | °C   |
| Power consumption           | $T_{amb} \leq 85\text{ °C}$ | $P_{tot}$   | 10                       | mW   |

**Note**

- Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect the device reliability.

| ELECTRICAL AND OPTICAL CHARACTERISTICS ( $T_{amb} = 25\text{ °C}$ , unless otherwise specified) |  |                   |      |          |      |                 |
|---|--|-------------------|------|----------|------|-----------------|
| PARAMETER   | TEST CONDITION   | SYMBOL            | MIN. | TYP.     | MAX. | UNIT            |
| Supply current (pin 3)  | $E_v = 0, V_S = 5\text{ V}$  | $I_{SD}$          | 0.65 | 0.85     | 1.05 | mA              |
|   | $E_v = 40\text{ klx, sunlight}$  | $I_{SH}$          |      | 0.95     |      | mA              |
| Supply voltage  |  | $V_S$             | 2.7  |          | 5.5  | V               |
| Transmission distance   | $E_v = 0$ , test signal see fig. 1, IR diode TSAL6200, $I_F = 400\text{ mA}$               | $d$               |      | 30       |      | m               |
| Output voltage low (pin 1)  | $I_{OSL} = 0.5\text{ mA}, E_e = 2\text{ mW/m}^2$ , test signal see fig. 1                  | $V_{OSL}$         |      |          | 100  | mV              |
| Minimum irradiance  | Pulse width tolerance: $t_{pi} - 5/f_0 < t_{po} < t_{pi} + 6/f_0$ , test signal see fig. 1 | $E_e\text{ min.}$ |      | 0.5      | 1    | $\text{mW/m}^2$ |
| Maximum irradiance  | $t_{pi} - 5/f_0 < t_{po} < t_{pi} + 6/f_0$ , test signal see fig. 1                        | $E_e\text{ max.}$ | 30   |          |      | $\text{W/m}^2$  |
| Directivity   | Angle of half transmission distance  | $\varphi_{1/2}$   |      | $\pm 45$ |      | deg             |


**TYPICAL CHARACTERISTICS ( $T_{amb} = 25\text{ °C}$ , unless otherwise specified)**


Fig. 1 - Output Active Low




Fig. 2 - Pulse Length and Sensitivity in Dark Ambient






Fig. 3 - Output Function




21394  $\Delta V_{S_{RMS}}$  - AC Voltage on DC Supply Voltage (mV)

Fig. 6 - Sensitivity vs. Supply Voltage Disturbances




21392

Fig. 4 - Output Pulse Diagram




20747

Fig. 7 - Sensitivity vs. Electric Field Disturbances



16925

Fig. 5 - Frequency Dependence of Responsivity



21407

Fig. 8 - Sensitivity vs. Ambient Temperature




Fig. 9 - Relative Spectral Sensitivity vs. Wavelength




Fig. 12 - Sensitivity vs. Supply Voltage




Fig. 10 - Horizontal Directivity





Fig. 11 - Vertical Directivity

### PACKAGE DIMENSIONS in millimeters





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.